




MioWORK[®] L110



Rugged enterprise computing

The L110 series from MioWORK are high performance enterprise tablets. Featuring an IP54 ingress-resistant design, the L110 series is ready for all-day use in the field. Workflows are optimised through the 10.1" capacitive touchscreen, users can see more content on the larger screen. Programmable hotkeys allow faster accuracy for key functions and applications. The L110 series includes dual-band WiFi for use on 5GHz enterprise networks, and the optional integrated 3G* means field workers are always connected. The L110 series offers uninterrupted use. With up to 8 hours battery life and a hot-swap user-replaceable battery, the L110 series perform 24/7 in demanding conditions.



Designed for professionals

- Hot swap battery for uninterrupted use
- Robust design
IP54 sealed / 1.2m drop resistant



Connected anywhere

- Connectivity with 3G *
- WiFi and Bluetooth® 4.0

** option*



Comprehensive using scenario

- Designed for multi-scenario, including:
Mobile POS, Table ordering, Field Service, Transportation and Logistics, Golf course navigation and Location based services.



Specifications **L110W**

L110

Display	10.1" 1280x800 WXGA TFT (400nits)	10.1" 1280x800 WXGA TFT (600nits)
Touch Panel	Capacitive Touch Screen	Capacitive Touch Screen
Platform	TI OMAP 4470 1.5GHz	TI OMAP 4470 1.5GHz
OS	Android 4.2.2	Android 4.2.2
Memory	1GB RAM / 16GB ROM	1GB RAM / 16GB ROM
Expansion	User accessible MicroSD up to 32GB SDHC	User accessible MicroSD up to 32GB SDHC
Wireless Interface	No Wireless WAN support (optional)	Wireless WAN Data UMTS/HSPA 800/850/900/1700/1900/2100 MHz GSM 850/900/1800/1900 Mhz; GPRS/EDGE Class 12
	WiFi 802.11 a/b/g/n	WiFi 802.11 a/b/g/n
	Bluetooth 4.0	Bluetooth 4.0
	GPS	GPS
	Accelerometer - auto rotation	Accelerometer - auto rotation
Sensors	Ambient light sensor	Ambient light sensor
	Vibrator	Vibrator
	N/A	Front: 1.2M fixed focus
Physical Interface	microUSB-B 2.0	microUSB-B 2.0
	USB Type A 2.0 (host and client)	USB Type A 2.0 (host and client)
	MicroSD slot	MicroSD slot
	SIM card slot: N/A	SIM card slot
	10 pogo pins connector	10 pogo pins connector
	Build-in MIC	Build-in MIC
	Build-in Speaker	Build-in Speaker
	Headset jack	Headset jack: N/A
	Power DC-Jack	Power Jack (compatible with waterproof vehicle charger only)
	Buttons	Side: Power, Volume up/down
Front: Function key x 4		Front: Function key x 4
Battery	Rear: Reset switch	Rear: Reset switch
	6720mAh battery, hot swappable	6720mAh battery, hot swappable
LED indicator	Battery life - up to 8 hours	Battery life - up to 8 hours
Environment	LED indicator X 2	LED indicator X 2
	IP54 and 1.2m drop resistant to plywood	IP54 and 1.2m drop resistant to plywood
	-10~+50°C operating temperature	-10~+50°C operating temperature
	-20~+70°C storage temperature (exclude LCM, Battery, Camera)	-20~+70°C storage temperature (exclude LCM, Battery, Camera)
	Humidity : 0~90%, Non-Condense	Humidity : 0~90%, Non-Condense
Standard Accessory	Altitude : Operating: 0~10,000ft	Altitude : Operating: 0~10,000ft
	Power adapter with power cord	Waterproof vehicle charger
Certification	USB cable	USB cable
	CE, FCC, VCCI, TELEC	CE, FCC, VCCI, TELEC
Weight	935g	950g
Dimensions	276.7x200x19.6mm	276.7x200x19.6mm

Applications	Mobile POS	Field Service
	Tabel ordering	Transportation and Logistics
		Golf course navigation
		Location based services